

GEOMAX Zone20 H basic rotating laser

Fully automatic horizontal laser with best price-performance ratio

Product number :27103000



Topfeatures

- Automatic self-levelling
- Easy to use and very reliable
- With manual tilt capability
- Laser class 1

All special features at a glance

- The GeoMax Zone Series rotating lasers are robust (IP67), versatile (900 m working range) and offer exceptional value for money.
- The Zone20 H horizontal laser is ideal for concrete and formwork work with self-levelling and manual tilting in two axes.
- Best application area: outdoor.

Description

The GeoMax Zone20 H is the entry-level model in the powerful Zone series of rotating lasers. It is robustly built and reliable in every respect. It offers all the functions required for professional or flexible use, making it interesting for all levelling, aligning or levelling applications. The horizontal laser allows manual adjustment of the tilt angle in two axes and its simple and well thought-out operating concept means it is quickly ready for use. The innovative Li-Ion battery concept enables up to 300 percent longer service life than would be possible with conventional NiMH batteries. With the included ZRB90 laser receiver, you can supplement the performance and increase the range up to 300 m.

Technical Details

Working area with receiver	Ø 900 m
Operating time	> 40 Hours
Weight	3060 g
Laser diode	visible 635 nm (red), class 1
manual tilt range	8 %
Dimensions	240 x 215 x 215 mm
Self-levelling range	± 6°
Power supply	2 alkaline mono cells (D), lithium-ion (Li-ion pack rechargeable)
Temperature range	-10 °C to +50 °C
Tolerance	± 0.75 mm per 10 m

Scope of supply

GeoMax Zone20 H, Receiver ZRB90, Transport case, Li-Ion battery with charger, Manual on CD, Quick start



MIT DEN BESTEN MESSEN

guide, Safety instructions