

NESTLE elevating tripod, medium aluminium version, self-impending, 200-394cm

The all-round tripod for every construction site

Product number :13402000



Topfeatures

- Millimetre-precise and convenient approach of the working height with the crank handle
- Outstanding ease of use
- Best quality in workmanship and material, thus suitable for many years of the hardest use
- Sturdy tread shoe for the toughest use

All special features at a glance

- Medium aluminium version, self-impending
- Model 13402000 features double side clamping for maximum clamping force. The patented side clamp acts in the direction of force without redirecting it. The play of the tripod is minimized by the double clamping, ideal for high working heights.
- With the help of the 35 cm crank stroke, a specific height can be approached very precisely. Due to the double reduction (crank stroke per revolution 1.2 cm), the crank can be moved comfortably even with heavy laser devices.
- Features a patented circumferential clamping band. The clamping acts on both the outer tubes and the centre profile. This ensures a constant clamping force in every extension position of the stand.
- If necessary, rubber caps can be folded over the tips of the tripod legs, which enables safe set-up on smooth surfaces and at the same time protects sensitive floors such as parquet or tiles when working indoors.
- The aluminium parts are anodised and therefore extremely weatherproof.
- The aluminium tubes slide easily and smoothly without jamming, the material is protected and the life of the tripod is extended.
- The plastic parts are made of glass-fibre reinforced polyamide and are therefore extremely robust.

Description

The NESTLE telescopic stand with centre column is ideal for positioning small to medium-heavy line and rotary lasers. On tripods with self-locking, the telescope is moved very easily and precisely to a desired height by means of a crank drive (crank stroke per revolution 1.2 cm). The main application of this tripod is metre level work or tasks with a high working height (200-394 cm). The integrated circular level ensures quick and easy set-up. With a 35 cm crank stroke, instruments can be set up steplessly and precisely to a desired height. The other technical features, such as stable tread shoes, spreader stop, eccentric clamping, anodised aluminium, plastic parts made of fibreglass-reinforced polyamide and high quality workmanship, ensure many years of use under the toughest conditions.

Technical Details

Working range at 1m tip distance	200-394 cm
Weight	7400 g
Crank stroke / connection all models	38 cm / 5/8"

Material	Aluminium
Transport dimension	209 cm

Scope of supply

Elevating tripod