

## NESTLE elevating tripod, medium aluminium version, self-impending, 105-290cm

### The all-round tripod for every construction site

Product number :13403000



#### Topfeatures

- Millimetre-precise and convenient approach of the working height with the crank handle
- Outstanding ease of use
- Best quality in workmanship and material, thus suitable for many years of the hardest use
- Sturdy tread shoe for the toughest use

#### All special features at a glance

- With the help of the 35 cm crank stroke, a specific height can be approached very precisely. Due to the double reduction (crank stroke per revolution 1.2 cm), the crank can be moved comfortably even with heavy laser devices.
- Model 13403000: With the supplied extension, a max. height of 290 cm can be reached.
- Features a patented circumferential clamping band. The clamping acts on both the outer tubes and the centre profile. This ensures a constant clamping force in every extension position of the stand.
- If necessary, rubber caps can be folded over the tips of the tripod legs, which enables safe set-up on smooth surfaces and at the same time protects sensitive floors such as parquet or tiles when working indoors.
- The aluminium parts are anodised and therefore extremely weatherproof.
- The aluminium tubes slide easily and smoothly without jamming, the material is protected and the life of the tripod is extended.
- The plastic parts are made of glass-fibre reinforced polyamide and are therefore extremely robust.

#### Description

The NESTLE telescopic stand is ideal for positioning small to medium-heavy line and rotary lasers. On tripods with self-locking, the telescope is moved very easily and precisely to a desired height by means of a crank drive (crank stroke per revolution 1.2 cm). The main application of this tripod is metre marking work or tasks with a high working height (105-290 cm). The integrated circular level ensures quick and easy set-up. With a 35 cm crank stroke, instruments can be set up steplessly and precisely to a desired height. The other technical features, such as stable tread shoes, spreader stop, eccentric clamping, anodised aluminium, plastic parts made of fibreglass-reinforced polyamide and high quality workmanship, ensure many years of use under the toughest conditions.

#### Technical Details

Working range at 1m tip distance	105-290 cm
Weight	5600 g
Crank stroke / connection all models	38 cm / 5/8"
Material	Aluminium
Transport dimension	127 cm

**Scope of supply**

Elevating tripod