


Leica Lino L6Gs

3x360° multi-line laser with Li-Ion battery

Product number :16730000



Topfeatures

- Range up to 50 metres
- Uninterrupted work thanks to Triple Power concept
- High visibility due to green high-power laser diodes
- Lithium-ion battery for up to 11 hours of operation
- Large self-levelling range

All special features at a glance

- 3 x 360° laser lines (2 x vertical, 1 horizontal)
- Suitable for construction site use due to robustness
- Laser power adjustable in three steps
- Self-levelling
- Fixed plumb point thanks to integrated base
- Triple power supply concept for uninterrupted work

Description

The Leica LINO L6G is a self-levelling multi-line laser with a green laser beam. The professional line laser has three 360° visible laser lines. Thin, sharp and highly visible 360° laser lines make this line laser ideal for demanding applications. Leica LINO L6G features a green laser that is proven to be more visible to human eyes. The vertical laser lines projected onto walls and ceilings can be easily adjusted once the plumb point has been set up. The integrated base of the line laser allows the intersection of the two vertical laser lines (plumb point) to be positioned as required. The laser lines can then be further aligned by $\pm 10^\circ$ without changing the plumb point. The triple power supply concept always allows uninterrupted work. The Leica LINO L6G can be powered with 3x AA batteries, Li-Ion rechargeable batteries or with a mains adapter (scope of delivery depends on article number). For better visibility or to save energy, the power of the laser lines can be adjusted in three steps (100%, 75% and 50%). Optionally available with magnetic adapter TWIST250 and wall mount UAL130.

Technical Details

Connection	¼
Working range	Ø 70 m (depending on lighting conditions)
Working area with receiver	Ø 140 m
Operational with receiver	yes
Operation temperature	-10°C to +50°C
Operating time	Li-Ion up to 11 hrs, alkaline up to 8 hrs
Accuracy	± 1.5 mm per 5 m
Weight	781 g
Laser horizontal	360°
Laser vertical	2 x 360°

Laser colour	green
Laser class	2
Dimensions	124 x 107 x 154 mm
Protection class	IP 54
Self-levelling range	$\pm 4^\circ$
Power supply	Li-Ion , 3 x AA alkaline, or mains adapter

Scope of supply

Leica Lino L6Gs, Li-Ion battery, charging power supply for Li-Ion battery, Battery compartment for alkaline, Quick reference guide, calibration certificate, green target, Bag