

Leica Lino L6Rs

Precise alignment 3x360° multi-line laser

Product number :16729000



Topfeatures

- Range up to 25 metres
- Uninterrupted work thanks to Triple Power concept
- High visibility due to red high-power laser diodes
- Large self-levelling range

All special features at a glance

- 3 x 360° laser lines (2 x vertical, 1 horizontal)
- Suitable for construction site use due to robustness
- Laser power adjustable in three steps
- Self-levelling
- Fixed plumb point thanks to integrated base
- Triple power supply concept for uninterrupted work

Description

The Leica LINO L6R is a self-levelling multi-line laser with a red laser beam. The professional line laser has three 360° visible laser lines. Thin, sharp and highly visible 360° laser lines make this line laser ideal for demanding applications. The vertical laser lines projected onto walls and ceiling can be easily adjusted after setting up the plumb point. The integrated base of the line laser allows the intersection of the two vertical laser lines (plumb point) to be positioned as required. The laser lines can then be further aligned by $\pm 10^\circ$ without changing the plumb point. The triple power supply concept always allows uninterrupted work. The Leica LINO L6R can be powered with 3x AA batteries, Li-Ion rechargeable batteries or with a mains adapter (scope of delivery depends on article number). For better visibility or to save energy, the power of the laser lines can be adjusted in three steps (100%, 75% and 50%). Optionally available with magnetic adapter TWIST250 and wall mount UAL130.

Technical Details

Connection	¼
Working range	Ø 50 m (depending on light conditions)
Working area with receiver	Ø 140 m
Operational with receiver	yes
Operation temperature	-10°C to +50°C
Operating time	Up to 25 hours
Accuracy	± 1.5 mm per 5 m
Weight	781 g
Laser horizontal	360°
Laser vertical	2 x 360°

Laser colour	red
Laser class	2
Dimensions	124 x 107 x 154 mm
Protection class	IP 54
Self-levelling range	$\pm 4^\circ$
Power supply	3 x AA alkaline

Scope of supply

Leica Lino L6Rs, 3x AA battery + battery compartment for alkaline, Red target plate, Quick reference guide, calibration certificate, Bag