

NESTLE Octoliner incl. receiver DECTO

Multi-liner for fast work

Product number :16101001



Topfeatures

- Manual inclination possible in one axis: $\pm 5\%$ electronically and additionally $\pm 8\%$ mechanically via the adjustable feet.
- Extremely simple operation for fast work.
- Clear and stable laser lines due to motorised self-levelling no wobbling of the line as with pendulum lasers.
- Versatility in use due to 360° horizontal line in combination with exactly perpendicular vertical planes.

All special features at a glance

- The NESTLE Octoliner creates a 360° horizontal line.
- 4 switchable vertical lines at a 90° angle form the upper plumb point.
- In addition, a perpendicular point downwards is created.
- The Octoliner has motorised self-levelling in a range of 4° .
- With the 5/8 thread connection, the laser can also be mounted on a tripod.
- The Octoliner is also suitable for use with a receiver for line lasers.
- Fine side drive for exact alignment of the vertical planes.
- Self-levelling can be switched off if necessary, e.g. to project crooked lines.
- Adjustable leg screws to compensate for unevenness outside the self-levelling range.

Description

The NESTLE Octoliner is an electronic, self-levelling cross line laser with superior accuracy. It can project four vertical lines at right angles to each other, as well as a 360° horizontal line, a plumb point on the floor and a laser cross on the ceiling with an accuracy of $\pm 1.5\text{ mm}/10\text{ m}$. It levels itself quickly and stably within a range of 4° . Its self-levelling is fast and stable within a range of 4° . Self-levelling can be switched off to project laser beams at an angle if required. Another advantage is its adjustable 360° pitch circle for easy angle measurements. The side fine drive supports the exact alignment of the vertical planes. Especially for outdoor work, we recommend the use of a DECTO receiver with mount.

Technical Details

Working range* without/with receiver	approx. 30 m / approx. 100 m
Working time	4 lines = 7 hrs / 2 lines = 8 hrs.
Weight	1520 g
Threaded connection	5/8"
Laser	635 nm, class 2
Dimensions	$\varnothing 15\text{ cm} \times 22\text{ cm}$
Optical angle	360° horizontal / 4 x vertical
Pulse mode	Yes
Protection class	IP54
Self-levelling	4°

Power supply

Integrated battery

Tolerance

 ± 1.5 mm per 10 m**Scope of supply**

Octoliner, DECTO receiver, Carrying case, Battery, Target board, Glasses, Charger