LEICA LINO L2P5G



Projects accurately, quickly and easily ideal for interior work

Product number :16728000



Topfeatures

- Extra long, good visible laser lines.
- 4 exactly right-angled laser points for plumbing and sighting.
- Self-levelling range ± 4°.
- Exact angles, perfect lines.
- Red laser beam (L2P5) or green laser beam (L2P5G).
- Works with optional receiver up to 80 metres.

All special features at a glance

- The LINO L2P5 combines line and point lasers in one instrument.
- With the L2P5, you always have the right instrument with you for all your tasks.
- The proven Leica optics and the large exit apertures ensure particularly long projections.
- In interior design, green light is often more easily perceived by the human eye. The LINO L2P5G projects green laser beams in laser class 2.
- Minor inaccuracies of up to $\pm 4^{\circ}$ when setting up are compensated for automatically.
- With the optional Lino RGR200 receiver, a range of up to 80 metres is possible.
- With triple power supply concept: power supply with Li-Ion battery (included), or included mains adapter or alkaline batteries.

Description

The Leica LINO L2P5G is a self-levelling multifunction laser that combines the advantages of cross line and point lasers in one device. The L2P5G is an absolute precision laser for a wide range of tasks such as levelling, plumbing, setting out and transferring measuring points. The green laser beam of the L2P5G class 2 is perceived by the human eye 4 times better than a comparable red beam and is therefore particularly suitable for interior work. Five laser points arranged exactly at right angles to each other form exact angles and perfect lines for drawing 90° angles. The integrated magnet allows the L2P5G to be attached to the Twist 360 magnetic adapter supplied and attached to magnetic components. The intelligent triple power supply concept makes the Leica LINO L2P5G universally applicable.

Technical Details

Battery	Li-Ion or 3 x AA
Accuracy	Points \pm 0.2, lines \pm 0.3 mm / m , mm / m
Weight	530 g
Laser colour	L2P5G = green
Laser class	2
Laser lines	vertical + horizontal
Laser points	above, below, right, left
Dimensions	110 x 60 x 100 mm
Reach	up to 35 m



Range with receiver	up to 80 m
Self-levelling range	± 4°
Tripod connection	1/4" (5/8")

Scope of supply

Lino L2P5G, Wall mount UAL130