

NESTLE DT-405L Theodolite Electronic Theodolite

For aligning and checking building axes

Product number :15104000



Topfeatures

- Large and easy to read digits in the display
- Tripod included
- Integrated function for testing and adjustment in the field

All special features at a glance

- With optical plummet
- The DT-400 series is an electronic theodolite with a digital angle measuring unit.
- Optionally with optical plummet (art. no. 15103000) or with laser plummet (art. no. 15104000).
- Both tubular and circular bubble for quick levelling.
- Switchable between degrees, GON and MIL.

Description

This lightweight, robust and very accurate electronic theodolite with an accuracy in angle measurement of 5" is particularly suitable for construction surveys. The DT-405 is also ideally suited for demanding tasks such as angle checks, alignments, inclinations and short levellings due to its excellent workmanship and easy operation. In addition, the DT-405L version is equipped with a visible laser plummet. This makes accurate set-up over a point easier than ever before.

Technical Details

Operation temperature	- 20°C to + 50°C °C
Accuracy laser plummet	± 1.0 mm / 1.5 m
Accuracy angle measurement	5 "
Weight	4300 g
Shortest target distance	approx. 100 cm
Dimensions	153 x 175 x 340 mm
Lens aperture	Ø 45 mm
Protection class / laser class	IP54 / 2
Enlargement	30x

Scope of supply

Electronic theodolite, Transport case, Charging station, Battery, Battery compartment for 4x AA batteries, Adjustment tool, Rain bonnet, Tripod