### **LEICA LINO L2P5**



# Projects accurately, quickly and easily ideal for interior work

Product number: 16727000



#### **Topfeatures**

• Extra long good visible laser lines.

- 4 exactly right-angled laser points for plumbing and sighting.
- Self-levelling range ± 4°.
- Exact angles, perfect lines.
- Available with red laser beam (L2P5) or green laser beam (L2P5G).
- Works with optional receiver up to 80 metres.

#### All special features at a glance

- The LINO L2P5 combines line and point lasers in one instrument.
- So you always have the right instrument with you for all your tasks.
- The proven Leica optics and the large exit apertures ensure particularly long projections.
- In interior design, green light is often more easily perceived by the human eye. The LINO L2P5 projects red laser beams, LINO L2P5G projects green laser beams, each in laser class 2.
- Minor inaccuracies of up to ± 4° when setting up are compensated for automatically.
- With the optional Lino RGR200 receiver, a range of up to 80 metres is possible.
- With triple power supply concept: power supply with Li-Ion battery (included), or included mains adapter or alkaline batteries.

#### **Description**

The Leica LINO L2P5 is a self-levelling multifunction laser that combines the advantages of cross line and point lasers in one device. The L2P5 is an absolute precision laser for a wide range of tasks such as levelling, plumbing, setting out and transferring measuring points. Five laser points arranged exactly at right angles to each other form exact angles and perfect lines for marking out 90° angles. The integrated magnet allows the L2P5 to be attached to the Twist 360 magnetic adapter supplied and to be attached to magnetic components. The intelligent triple power supply concept makes the Leica LINO L2P5 universally applicable.

#### **Technical Details**

Battery	Li-Ion or 3 x AA
Accuracy	Points $\pm$ 0.2, lines $\pm$ 0.3 mm / m , mm / m
Weight	530 g
Laser colour	L2P5 = red,
Laser class	2
Laser lines	vertical + horizontal
Laser points	above, below, right, left
Dimensions	110 x 60 x 100 mm
Reach	L2P5 up to 25 m



Range with receiver	up to 80 m	
Self-levelling range	± 4 °	
Tripod connection	1/4" (5/8")	

## **Scope of supply**

LINO L2P5-1, Adapter Twist 360, Li-Ion battery, Charger, Target board, Suitcase