GEOMAX Receiver ZRD105 digital



The best digital technology in a robust housing.

Product number :27402000



Topfeatures

- IP67 protection class for the toughest use.
- Operation temperature -20°C to +50°C.
- Suitable for all Zone rotating lasers.
- Suitable for the working range of $\ensuremath{\varnothing}$ 900 m.
- Audible and graphic display.

All special features at a glance

- The ZRD105 Digital Laser Receiver. Best digital technology in a robust housing.
- Double-sided display and numerical display in five precision levels.
- The numerical display shows the laser distance in real numerical values.

Description

The GeoMax Zone series includes a total of four laser receivers that complement and enhance the performance of the Zone rotating lasers. The ZRD 105 Digital offers the best digital display technology in a robust housing. The fully equipped top receiver for precise results leaves nothing to be desired and impresses with its dual display that is supported by adjustable LED and audio signals. The flash suppression, the double-sided display and the numerical display, which shows the laser distance in real numerical values, make the ZRD 105 a real professional tool on the construction site.

Technical Details

Operation temperature	- 20°C to + 50°C °C
Reception	Display and sound
Detection zone	105 mm
Weight	320 g
Dimensions	175 x 80 x 30 mm
Numeric	90 mm
Precision levels	± 0,5, ± 1, ± 2, ± 3, ± 5 mm
Reach	Ø 900 m
Protection class	IP67

Scope of supply

GEOMAX Receiver ZRD105 digital, Holder, Batteries