NESTLE MIT DEN BESTEN MESSEN

NESTLE laser rod with sliding adapter screw clamp

Ideal for level work with rotating lasers

Product number:18701000



Topfeatures

- Easy and quick handling for reliable level control.
- Low weight for fatigue-free work.

Weatherproof

All special features at a glance

- Easy-to-carry aluminium profile fits perfectly in the hand.
- Silver anodised aluminium profile, protected against all weather conditions.
- Quick fixation of the laser bar at the correct height with a locking screw.
- Easy determination of level differences.

Description

The laser batten for receivers of rotating lasers is the optimal accessory for determining a level without calculating. The easy-to-carry anodised aluminium profile fits perfectly in the hand and is protected against all weather conditions. This laser level is supplied with a sliding adapter with screw clamp. The sliding adapter simplifies readings on the laser staff. The two-colour division of the staff makes it easier to determine a level. The upper part is divided in descending order from 50 cm to 0 cm and has a red background. The lower part, on the other hand, has a silver background and is divided in ascending order from 0 cm to 50 cm. In this way, deviations from the level can be read easily and without calculation. The laser bar with the receiver at the zero mark is extended to the receiving level and fixed. Another scale on the front shows you the height of the zero level to the ground point of the staff. Ideal for all work with rotating lasers.

Technical Details

Adapter	with sliding adapter / screw clamp
Weight	1300 g
Length	130 - 240 cm

Scope of supply

Laser rod, Bag